

LED Downlight Adjusted Recessed Round Slot

1LARRxxxS



1LARR3X2S

1LARR7X4S







1LARR013S

1LARR026S

1LARR033S

1LARR052S

Specification

Description	1LARR3X2S	1LARR7X4S	1LARR013S	1LARR026S	1LARR033S	1LARR052S
Dimension	 ø60mm x 48mm ☞ 48mm(Cut out)	 ø60mm x 82mm ☞ 48mm(Cut out)	 ø75mm x 103mm ☞ 75mm(Cut out)	 ø130mm x 129mm ☞ 115mm(Cut out)	 ø144mm x 162mm ☞ 130mm(Cut out)	 ø144mm x 172mm ☞ 130mm(Cut out)
Power Consumption	3.2W	7.4W	13W	26W	33W	52W
Beam Angle	24°, 36°	24°, 36°	15°, 28°, 40°	15°, 28°, 40°, 50°	15°, 30°, 55°	15°, 30°, 55°
Lumen(lm)	360 lm	630lm	1200lm	2360lm	3266lm	4417lm
OUTPUT	350 mA	700mA	350mA	700mA	1000mA	1400mA
CCT(K)	3000K, 4000K, 5000K					
LUX LEVEL @3m	100 lux(24°), 80 lux(36°)	168 lux(24°), 134 lux(36°)	327 lux(15°), 281 lux(28°), 197 lux(40°)	899 lux(15°), 677 lux(24°), 396 lux(40°), 291 lux(50°)	1078 lux(15°), 646 lux(30°), 280 lux(55°)	1038 lux(15°), 722 lux(30°), 359 lux(55°)